

Amateur Division

No: 17-0710

Product Upgrade Information – FT-2980R

July 12, 2017

FT-2980R 80W FM VHF Mono Band Mobile Transceiver

We are pleased to announce the new VHF Mono Band FM Analog Mobile Transceiver – **FT-2980R**.

As its model name suggests, the new **FT-2980R** arrives with the solid feature configuration and mechanical toughness of the ever popular FT-2900R - with a superior output power that is upgraded to **80 Watts!!**

With the new **FT-2980R**, four output power settings - 80W, 30W, 10W and 5W – are selectable, allowing each user to choose the power they want for their operating style and situations. A Massive Heatsink guarantees a solid 80 Watts of RF Power with no cooling fan needed. Thanks to a loud 3 Watts of audio output, the operator can enjoy reception - even in noisy environments.

Other useful functions included are; Alphanumeric Channel Display; 200 Memory Channels; CTCSS and DCS Encode/Decode Built-in; Versatile Scanning Capability; Wide/Narrow Deviation Selection, Interactive Programming Menu, and so on. For any further detailed specifications, please refer to the attached sheet.

Please also be informed that we will be discontinuing the FT-2900R along with the launch of the new **FT-2980R**. Our FT-2900 has enjoyed many rich years of tremendous sales and we sincerely appreciate your long patronage. We are assured that the new **FT-2980R** will continue to serve the customer base - who have long been attracted to the specifications, features and reliability of the FT-2900R – as well as continue to contribute to your business.

The FT-2980R will be available soon (August 2017) and we are accepting your orders, starting now!

FT-2980R

144MHz 80W FM Single Band Mobile Transceiver

Heavy Duty FM Single Band Mobile

Radio Features:

- Massive Heatsink guarantees 80 Watts of RF Power with No Cooling Fan Needed
(Four selectable power output levels are provided: 80/30/10/5 Watts)
- Loud 3 Watts of Audio Output for noisy environments
- Large 6 Digit Backlit LCD ensure excellent visibility
- Excellent Receiver Performance
- Alpha-Numeric Channel Display
- 200 Memory Channels for serious users
- CTCSS and DCS Encode/Decode Built in
- Versatile Scanning Capability
- WX Channels with "Severe Weather" Alert
- Smart Search Operation
- DTMF Direct Access Microphone Included
- Wide/Narrow Deviation Selection
- RF-Squelch
- Interactive Programming Menu
- Supply Voltage Display
- 4-level Display Dimmer
- Dual Watch



FT-2980R

Supplied Accessories:

DTMF Microphone(MH-48A6JA)
Mobile Mounting Bracket(MMB-83)
DC Power Cord w/Fuse
Spare Fuse (25 A)
Standing Foot
Operating Manual
Warranty Card

Specifications:

Frequency Ranges: RX 136 - 174 MHz

TX 144 - 148 MHz

Circuit Type:	Double-Conversion Superheterodyne
Modulation Type:	F3E(FM), F2D(PACKET)
Output Power:	80 W/30W/10W/5W
Memory Channels:	200
Case Size(W x H x D):	6.3" x 2.0" x 7.3" (w/o Knobs)
Weight:	4.2 lbs
Qty in Master Carton:	5
Warranty:	3 Years